【 - 인용빌명1 : 일본공개특허공보 평13-042827호(2001.02.16) 】

THIS PAGE BLANK (USPTO)

(19)日本国**特許計 (J P)**

(12)公開特許公報(A)

(11)特許出屬公園為母

特第2001-42827

(P2001-42827A)

(43)公開日 平成13年2月16日(2001.2.10)

America						
(U1)Int.Cl,	和别心计	•	f i		5	デーヤコート (493等)
GOBG 3/30		:	G09G	3/30	· ĸ	5 C 0 8 0
GO 9 F .9/30	365	·	GOSF	9/30	3652	5 C G 9 4
G 0 9 G 3/20	811		G 0 9 G	3/20	61111	
	833				623A	•
	642	•			642B	

帯楽権家 未婚派 湯水母の数15 ひし (会 13 点)

(21)出籍署钤

(22)担期日

特類平11-219782

平成11年8月3日(1999.8.3)

(71) HISTA. 000005016

バイオニア株式会社

東京都自居区日第1丁目4番19

(72)発明者 石墩 東一

埼田県第ヶ島市富士見6下回1番1号 パ

イマニア株式会社総合研究所内

(72)発明者 土山 正美

斯茨米州ヶ島市原士県6丁月1番1号 パ

イオニア株式会社総合研究所内


(74)代納人 100079119

升理士 選村 元李

教徒質に続く

(54) 【発射の名称】 ディスプレイ執着及びディスプレイパネルの影動創館 (57) 【契约】

「課題」 陽極線ドライブ関係を報数の1 Cチップで構築した関にもディスプレイパネル上での発光解素を物一にすることが出来るディスプレイパネルとの発光解素を物ーにすることが出来るディスプレイが表現がディスプレイパネルの認めを提供することを自めとする。 「解決手段」 各々が、ディスプレイパネルの発光者を発光させる発光態動電流を発生して、このディスプレイパネルの第1 電磁線に関係する複数の発光型動電流解音流解する複数の服動四級からなり、これら駆動・電流を持っていませば、他の配動動物が発生した光光を動電流のでするとでは、他の配動動物が発生した光光を動電流のできた。この胚動四段が発生ででき発光変動を流のできませないて、この胚動四段が発生すべき発光変動を流のできませないで、この胚動四段が発生すべき発光変動を流のできませないで、この胚動四段が変化する。



PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2001-042827

(43)Date of publication of application: 16.02.2001

(51)Int.Cl.

G09G 3/30 G09F 9/30

G09G 3/20

(21)Application number: 11-219782

(71)Applicant: PIONEER ELECTRONIC CORP

(22)Date of filing:

03.08.1999

(72)Inventor: ISHIZUKA SHINICHI

TSUCHIDA MASAMI SAKAMOTO TSUYOSHI


OCHI HIDEO "

(54) DISPLAY DEVICE AND DRIVING CIRCUIT OF DISPLAY PANFI

(57)Abstract:

PROBLEM TO BE SOLVED: To make light emitting luminance on a display possible to be uniform at the time of constituting an anode line drive circuit of plural IC chips by controlling the amount of light emitting driving current to be outputted by a first anode line driven circuit based on the light emitting current outputted by a second anode line drive circuit.

SOLUTION: A current source (transistors Q1 to Qm) is provided in anode line drive circuits 21 and 22 to generate a light emitting driving current. Moreover, a driving current control circuit CC, which maintains the light emitting driving current at an amount of current corresponding to an inputted control current, is provided. Furthermore, a control current output circuit CO is provided to output a light emitting driving current itself as a control current. At the time of driving anode lines of a display panel by plural anode line drive circuits 21 and 22 constructed in individual IC chips, the first and anode line driving circuit 21 controls the amount of light



emitting driving current to be outputted based on the actually outputted light emitting drive current by a second anode line drive circuit 22.

LEGAL STATUS

[Date of request for examination]

19.09.2003

[Date of sending the examiner's decision of

22.07.2004

rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision 2004-17316

of rejection]

[Date of requesting appeal against examiner's 20.08.2004

decision of rejection]

[Date of extinction of right]

Copyright (C): 1998,2003 Japan Patent Office

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
☐ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.